

Residential Electrical Metering

Advanced ANSI metering for the Smart Grid



Aclara's I-210 product line continues the tradition to bring innovative and flexible technology solutions that cover all your metering needs from basic electronic energy-only meters to highly-flexible smart metering solutions that provide advanced functionality to meet the evolving Smart Grid system needs.

Aclara's family of meters go beyond meeting your complex business challenges. The advanced, powerful and easy-to-use meters give you an extra edge in the energy business. You can look forward to realtime instrumentation, power quality monitoring and easy access to critical information. All these add up to give you higher productivity, improved efficiency and reduced energy costs.

KEY BENEFITS

- Reliable and accurate cash register for utilities
- AMR/AMI Plug-n-Play functionality
- Multiple communication technologies tied to AMI systems provide reliable data in a timely manner
- Smart metering functions such as Time of Use demand metering and service switch capabilities
- Demand side management through pre-payment and demand limiting features
- Advanced functions such as reactive measurement and, IEEE reliability indices measurement
- Robust meter security and standards compliance

COMMUNICATIONS

- Broad AMI/AMR Plug-n-Play options - RF Mesh, Power line carrier, Cellular, etc
- Allows interchangeability of AMR/AMI Plug-n-Play options
- Supports connectivity and integration with 3rd party communications solutions providers

Single Phase Meters



I-210+c FULL FEATURED, SMART GRID ENABLED METERING

This is Aclara's flagship residential meter product, offering demand, load profile, TOU, service switch, and a full complement of communication options.



I-210+ VALUE PACKED SMART GRID FUNCTIONS

World class accuracy and reliability in a solid-state kWh meter platform package. Available with a service switch, as well as a wide array of communications options.

SMART CONFIGURATION

- Ability to customize advanced metering options to suit customer's needs
- Configure load profile, time of use and demand metering capabilities
- Versatile programming Softswitches allowing the selection of advanced functionality such as power quality measurement and reactive power measurement
- Service Switch option improves operational efficiency and addresses issues such as demand side management, remote repayment systems, and controlled outage restoration

RELIABILITY

- Robust revenue-grade watt-hour and demand meters
- Based on Aclara's cutting edge technology providing typical 0.2% accuracy, and reliability
- Enable utilities with tools to lower operational cost and provide accurate metering solutions

RELIABLE METERING

In this dynamic time of regulatory scrutiny and customer engagement, you can be assured of the product and the company behind the product. We have ANSI and ISO certified labs to ensure that our product design and manufacturing processes yield a robust product every time.

Our testing procedures go well beyond the ANSI and IEC requirements for which we design to, including some of the most aggressive internal standards in the market place today. We now have included world-class Radio Frequency (RF) communications expertise to ensure that our meter products are hardened to withstand even the harshest of RF environments without sacrificing the quality or integrity of the metrology or the communications technology.

ACCURATE & DEPENDABLE

Typically measured at +/- 0.2%, the Aclara I-210 family of meters provides best-in-class capabilities for accuracy. Combined with the low starting watts, the utility can have confidence in the metered value and measured electricity usage.

INTEGRITY OF SUPPLY

Having a partner that can provide assurance in supply is critical when a utility begins a mass deployment of meters. Aclara's process focus and rigor around supply chain excellence minimizes the risk to the utility, giving them confidence to manage installation crews and provide accurate scheduling to customers.

BROAD COMMUNICATIONS SUPPORT

The I-210 family has been designed to allow for the interchangeability of AMR/AMI modules and cover the broadest range of possible AMI communication technologies including RF Mesh, Cellular, Power Line and Ethernet. Modules can be added at the Aclara factory, after the fact, or replaced with another compatible module if the meter is redeployed.



ACLARA'S iiDEAS® OPERATIONAL DATA MANAGEMENT PLATFORM

iiDEAS integrates head-end and meter data management into one unified application. Ideas aggregates AMI meter data with existing utility applications and offers a single, customizable interface for personnel to access the critical data they need to better manage their distribution infrastructure, optimize operations and improve service reliability.

AMI meter data is significantly enhanced by the aggregation of data from such systems as GIS, OMS, CIS and SCADA. iiDEAS uses standard interfaces such as MultiSpeak and CIM to integrate with these systems. iiDEAS also provides a range of advanced analytics including loss analysis, transformer analysis, voltage analysis and fault detection and localization.

Full featured, Smart Grid Meter

I-210+c

SMART GRID ENABLED, CONSUMER FRIENDLY METERING

Aclara's most advanced residential electricity metering product line, the I-210+c, delivers Smart Grid capability for today and the future. Derived from our industry leading commercial and industrial product line, the kV2c, the I-210+c benefits from our advanced metrology capability and lessons learned from over 10 years of solid state metering design. All the way down to the advanced microprocessor, the I-210+c contains much of the advanced polyphase functionality that Aclara has been known for. We have also added capability that makes the I-210+c the referenced residential product line in the industry.

CAPABILITY

Designed for today's dynamic rate structures, the I-210+c provides capability for demand, load profile, and TOU recording, along with a number of other power quality and demand response related functions. Configurable to support various metering quantities, this meter supports delivered (+), received (-), and net metering for distributed generation.

ADVANCED FUNCTIONALITY

With the addition of the fully rated 200 amp service switch, the meter is capable of pre-payment metering without all the historical cost associated with card readers or other legacy pre-payment technology. Load limiting and emergency conservation modes set this meter apart when working in conjunction with a demand response program. Having the capability to be remotely configured, as well as being firmware upgradeable, this product serves today's needs, as well as tomorrow's evolving requirements.

COMMUNICATIONS

Designed to specifically accommodate the communications technology required to support a Smart Grid, the I-210+c has the same electrical and mechanical interface as our I-210+ platform, making communications interchangeable and interoperable between these two residential metering platforms.



FEATURES & BENEFITS

- Customize advanced metering options through SoftSwitches
- AMR/AMI Plug-n-Play designed to accommodate:
 - Radio Frequency Mesh (RF Mesh)
 - Radio Frequency Point-to-Multipoint
 - Cellular communications
 - Ethernet
- Advanced functionality such as: time-of-use, insensitive demand, load profile recording, event logging, voltage sag/swell recording
- Typical accuracy: within +/- 0.2%
- Service Switch to improve operational efficiency and address issues such as:
 - Demand side management
 - Remote prepayment systems
 - Controlled outage restoration
- Low starting watts; capture energy consumption at levels typically not registered by electromechanical meters
- Low burden, which minimizes utility system losses
- Patented tamper algorithm to detect tamper-by-meter inversion
- Meets or exceeds ANSI C12.1, C12.10, C12.20, C37.90.1 and UL2735

AMR/AMI PLUG AND PLAY COMMUNICATIONS

Multiple communication options on the I-210+c allows greater customer choice. Ideally optimized for RF Mesh, PLC, 3G/4G point-to-point communication technologies, the I-210+c can cover a wide variety of communication scenarios.



I-210+c

Utility Communication

- Radio Frequency Mesh (RF Mesh),
- Power Line Communications (PLC),
- Cellular Communications
- Ethernet



Utility Monitoring & Control Center

Value packed, Smart Grid Meter

I-210+

LOAD MANAGEMENT

The I-210+ is one of the most popular single phase meters among US utilities for residential metering installations. Equipped with a fully-rated 200A service switch, this meter platform is ideal to provide basic load management functionality.

RELIABILITY

The I-210+ has enjoyed tremendous success in the marketplace for smart meters, with over 10 million units shipped since 2009. This product is the industry benchmark for quality and reliability, having passed both internal and external validation tests for billing accuracy. At Aclara, we have an unprecedented testing and validation process to ensure that our products are robust and exceed the industry standard ANSI requirements.

We have substantial expertise in wireless communications and the testing that is required to ensure that our meters perform flawlessly, even in the harshest of radio frequency (RF) environments.

COMMUNICATIONS

The I-210+ has the same electrical and mechanical interface as our I-210+c platform, designed to specifically accommodate Smart Grid communications technology, making communications interchangeable and interoperable between these two residential metering platforms. Multiple RF Mesh and PLC communication technologies are supported with a newly updated power supply.



FEATURES & BENEFITS

- AMR/AMI Plug and Play designed to accommodate: RF Mesh, RF Point-to-Multipoint, PLC, Ethernet
- Typical accuracy: within +/-0.2%
- Service Switch to improve efficiency and address:
 - demand side management
 - remote prepayment systems
 - controlled outage restoration
- Low starting watts; capture energy consumption at levels
- typically not registered by electromechanical meters
- Low burden, which minimizes utility system losses
- Meet or exceeds ANSI C12.1, C12.10, C12.20, C37.90.1

Factory Integrated Communication Options for I-210+ and I-210+c Meters

AMI Technologies	Type	I210+	I210+c
Aclara TWACS	PLC	•	
Aclara Synergize® RF	RF P2MP	•	
Itron Single ERT HP (54-56ESS)	1-way RF AMR	•	
Itron Triple ERT HP (57ESS)	1-way RF AMR		•
Itron EVDO & HSPA	Cellular (3G)		•
Sensus Flexnet™	RF P2MP		•1
Silver Springs Networks© NIC 410	RF Mesh		•1
Silver Springs Networks© NIC 510	RF Mesh		•1
Silver Springs Networks© MicroAP	Cellular & RF Mesh		•1
Trilliant RPMA	RF P2MP	•	•1
Trilliant SecureMesh™	RF Mesh	•	•

Note 1 : Optional UL Certified Meter

Full featured, Secure Metering Software

MeterMate

SMART GRID ENABLED, CONSUMER FRIENDLY METERING

Aclara's innovative MeterMate™ software suite enables meter administrators to easily configure and manage Aclara meters. Each software component in the MeterMate suite is optimized to address the different aspects of a meter's lifecycle. MeterMate program creation software enables the user to effortlessly configure the meter's basic and advanced functionality, ranging from creating a simple demand program and setting up the meter display to configuring the meter's I/O and alerts. With MeterMate reading and programming software, a user can read, program and perform real-time instrumentation and power quality monitoring on a meter, via a variety of different communication methods such as local OPTOCOM, remote telephone, RS-232/485 and IP communications.

The MeterMate software also supports many functions such as:

- Analysis of load profile data
- Firmware upgrades
- Exporting of meter data to the MV-90 HHF format
- Configuration for automatic remote meter reading
- Direct table reads
- Conversion of meter configuration to an XML file format for AMI over-the-air configuration
- Comparison of a configuration from the database to a configured meter
- Opening and closing the meter service switch
- Importing and exporting of load profile data, event log data, configurations and security codes



FEATURES & BENEFITS

- One software suite to configure and read from the Aclara portfolio of meters: kV family, I-210 family and SGM3xxx family
- Supports the ANSI C12.19 communication protocol
- Multiple methods to communicate with meters: USB & RS232 OPTOCOM, RS485, Modem
- Modular configuration workflow that enable the reuse of frequently used configuration settings and measurements
- Various reports to display information for meter management, auditing, billing and monitoring power quality
- Command line interface and batch-control enabling automated and scheduled meter operations
- Configurable role-based access control security

Residential Meter Selector

	Product Characteristics	I-210+ Basic Energy	I-120+c																																										
1	Meter Functionality	<ul style="list-style-type: none"> Real Energy Consumption Management 	<ul style="list-style-type: none"> Real Energy Consumption Management Reactive Energy Consumption Measurement Apparent Energy Consumption Measurement Voltage Measurement (Min, Avg, Max) Sag/Swell Measurement Outage Count and Duration 																																										
2	ANSI Models	<table border="1"> <thead> <tr> <th>FORM</th> <th>CLASS</th> <th>VOLTS</th> </tr> </thead> <tbody> <tr> <td>1S</td> <td>100</td> <td>120 & 240</td> </tr> <tr> <td>2S</td> <td>200 & 320</td> <td>240</td> </tr> <tr> <td>3S & 3CS</td> <td>20</td> <td>120 & 240</td> </tr> <tr> <td>4S</td> <td>20</td> <td>240</td> </tr> <tr> <td>12S</td> <td>200 & 320</td> <td>120 & 240</td> </tr> <tr> <td>25S</td> <td>200 & 320</td> <td>120 & 240</td> </tr> </tbody> </table>	FORM	CLASS	VOLTS	1S	100	120 & 240	2S	200 & 320	240	3S & 3CS	20	120 & 240	4S	20	240	12S	200 & 320	120 & 240	25S	200 & 320	120 & 240	<table border="1"> <thead> <tr> <th>FORM</th> <th>CLASS</th> <th>VOLTS</th> </tr> </thead> <tbody> <tr> <td>1S</td> <td>100</td> <td>120 & 240</td> </tr> <tr> <td>2S</td> <td>200 & 320</td> <td>240</td> </tr> <tr> <td>3S & 3CS</td> <td>20</td> <td>120 & 240</td> </tr> <tr> <td>4S</td> <td>20</td> <td>240</td> </tr> <tr> <td>12S</td> <td>200 & 320</td> <td>120 & 240</td> </tr> <tr> <td>25S</td> <td>200 & 320</td> <td>120 & 240</td> </tr> </tbody> </table>	FORM	CLASS	VOLTS	1S	100	120 & 240	2S	200 & 320	240	3S & 3CS	20	120 & 240	4S	20	240	12S	200 & 320	120 & 240	25S	200 & 320	120 & 240
FORM	CLASS	VOLTS																																											
1S	100	120 & 240																																											
2S	200 & 320	240																																											
3S & 3CS	20	120 & 240																																											
4S	20	240																																											
12S	200 & 320	120 & 240																																											
25S	200 & 320	120 & 240																																											
FORM	CLASS	VOLTS																																											
1S	100	120 & 240																																											
2S	200 & 320	240																																											
3S & 3CS	20	120 & 240																																											
4S	20	240																																											
12S	200 & 320	120 & 240																																											
25S	200 & 320	120 & 240																																											
3	Soft-Switches to upgrade meter function	<ul style="list-style-type: none"> Optional Softswitches can be loaded in the factory or by the user to activate advanced functions O — Activates communication capability with AMR/AMI modules S2 — AMI/AMR calculated demand displayed on meter LCD V2 — Simple Voltage Event monitor in addition to a display of RMS momentary voltage on the 3 lower LCD digits 	<ul style="list-style-type: none"> Optional Soft-switches can be loaded in the factory or by the user to activate advanced functions A2 — Activates communication capability with AMR/AMI modules E2 — Activates Event Log Recording (up to 200 Events) K2 — Activates Reactive/Apparent Energy Consumption recording N2 — Activates Demand Q2 — Activates Instrument Recording R2 — Activates LP recording (up to 4 channels) T2 — Activates TOU recording V2 — Activates Sag/Swell monitor and recording 																																										
4	AMR Interface (Factory enabled or installed by customer)	<ul style="list-style-type: none"> Quadrature Pulse SPI Format-1 data SPI Format-2 data PSEM Communications 	<ul style="list-style-type: none"> PSEM Communications 																																										
5	Energy Accumulation	<ul style="list-style-type: none"> Must specify at time of order either: <ul style="list-style-type: none"> Delivered only Delivered + Received Delivered – Received Received only Customer can change selection later using MeterMate 	<ul style="list-style-type: none"> Specified at time of order for factory programmed meters or configured by the customer using MeterMate. Any two or four of the following energy measurements can be selected: <ul style="list-style-type: none"> Delivered only kWh Received only kWh Delivered + received kWh Delivered – received kWh Lagging only kvarh; requires K2 Soft-switch Leading only kvarh; requires K2 Soft-switch Lagging + Leading kvarh; requires K2 Soft-switch Lagging - Leading kvarh; requires K2 Soft-switch Phasor apparent VAh; requires K2 Soft-switch 																																										
6	Cycle Insensitive Demand	<ul style="list-style-type: none"> Not available 	<ul style="list-style-type: none"> Requires T2 & N2 Soft-switches to be enabled Provides an alternative method for calculating the maximum demand in meters equipped with one-way AMR system. The meter maintains the daily maximum demands and the two peaks for the period. Demand is calculated using the programmed method (Block, rolling or thermal). The daily maximum demands are stored in a circular queue. Each entry in the circular queue contains a date 																																										
7	Power Quality	<ul style="list-style-type: none"> With V2 Softswitch enabled, provides a count of Sag/Swell Events. Value and duration thresholds are programmable 	<ul style="list-style-type: none"> With Q2 and R2 Softswitches enabled, Min, Max and Average Voltage recording is possible. With V2 Softswitch enabled, provides counts and magnitude recording of Sag/Swell Events with date and time stamped. Value and duration thresholds are programmable. This Sag/Swell Event Log is separate from the Event Log recording provided by the E2 Softswitch With E2, R2 and T2 Softswitches enabled, recording of sustained and total outage counts and duration is possible to permit calculation of IEEE Reliability indices. 																																										
8	Back-up power	<ul style="list-style-type: none"> Not available 	<ul style="list-style-type: none"> Back-up power is used to maintain the meter clock during outages. If the R2 or T2 softswitch is required, one of the following back-up power options must be selected. <ul style="list-style-type: none"> Battery Supercap Batteryless operation. For batteryless operation, the AMI system must be able to re- synchronize the meter clock after a power outage 																																										
9	Service Switch (provide remote controllable disconnection and reconnection of electrical service for residential applications)	<ul style="list-style-type: none"> A switching device intended to provide remote controllable disconnection and reconnection of electrical service for residential applications. Factory installed option, specify at time of order. Full functionality requires two-way AMI module Switch is installed under standard size cover Typical applications include: <ul style="list-style-type: none"> Remote disconnect and reconnect of service Energy conservation demand limiting Demand limiting as an alternative to service disconnection Prepayment metering Outage management/restoration Note: Energy conservation demand limiting and prepayment metering functionalities are not available on forms 12S and 25S. 	<ul style="list-style-type: none"> A switching device intended to provide remote controllable disconnection and reconnection of electrical service for residential applications. Factory installed option, specify at time of order. Full functionality requires two-way AMI module Switch is installed under standard size cover Typical applications include: <ul style="list-style-type: none"> Remote disconnect and reconnect of service Energy conservation demand limiting Demand limiting as an alternative to service disconnection Prepayment metering Outage management/restoration 																																										

Technical Specifications

I-210+ c

Basic Functions

- Single Phase Demand Meter
 - Energy management, 4 quantities
 - Demand, block or rolling demand
 - Fundamental plus harmonic measurements
 - Bi-directional energy measurements
- Load Profile recording
- Time of Use Billing Measures
- Four Energy options (Delivered, Received, Delivered+Received, Delivered -Received)
- Tamper detect capability
- Broad communication module options
- Network applications
- Models available for 120 or 240 volt CL 20, CL 100, 200, CL 320 applications.
- 50 or 60 Hz operation

Optional Functions

- Factory integrated Service Switch Capability

Soft-Switch Functions

- The Alternate Communication Soft-switch allows a communication option board to communicate with the meter
- E₂ Soft-switch
 - The Event Log Soft-switch allows the meter to track the most recent 200 events. Use MeterMate™ Program Manager, Diagnostics Editor, to select the event types to be logged and how many occurrences should be tracked, up to a maximum of 200 events. Date and time stamps are included on logged events for Demand/LP or TOU meters
- K₂ Soft-switch
 - The kVA and kvar Soft-switch adds kVA(h) and kvar(h) measurement capability.
- N₂ Soft-switch
 - The Demand (N₂) Soft-switch adds billing demand calculations.
- Q₂ Soft-switch
 - The Instrumentation Measurements Soft-switch enables
 - Voltage (L-N): VA (max, min store) for summations, demand, and load profile recording
 - RMS voltage measurement for reading and display
 - Low potential caution
 - Temperature (max, min,avg) load profile recording
- T₂ Soft-switch
 - The time-of-use soft-switch enables TYOU operation
 - Up to four TOU periods and four Seasons
 - Up to three daily rate schedule types and one holiday schedule
 - Up to 80 TOU schedule set points
 - Up to 50 programmable dates
 - Holidays, season changes, Daylight Savings Time (DST), self-read, and demand reset
 - Perpetual calendar handles most dates
 - Up to two billing and two demand measures per TOU period
 - Self-read actions on specified dates, with o4r without a demand reset
- V₂ Soft-switch
 - The voltage Soft-switch activates Sag/Swell monitor and recording

Accuracy

- Typical Accuracy: Within +/- 0.2%
- Starting Watts: 12W @ 240V, 6W @ 120V
- Typical Watt Loss: 0.7 Watts

Rating

- Voltage: 120V -240V
- Current: Class 100, Class 200, Class 320, Class 20
- Frequency: 50 or 60 Hz

Cover Options

- Polycarbonate over with molded sunshield
 - Plain cover without RESET or “D” ring
 - With Optocom “D” ring
 - With RESET latch and “D” ring

Operation Range

- Voltage: +/- 20%
- Operates over a broad temperature range (-40C through +85C under the cover)

Available Models


- ANSI Form 1S, 2S, 3S, 4S, 12S, 25S
- CL20, CL100, CL200, CL320

Applicable Standards

- Performance meets or exceeds industry standards
- ANSI C12.19
- ANSI C12.1
- ANSI C12.10
- ANSI C12.20
- ANSI C37.90.1
- UL 2735

LCD Display

- 6 large characters to display the main programmed metering quantities



Weights and Dimensions

Dimensions
6.94 in. Max



5.25 in. Max

Approximate Weight

- Meters with service disconnect
 - Individual meter 2.0 - 2.4 lbs
 - 4 meter pack 9.0 - 10.6 lbs
 - Pallet (120 meters) 285 - 340 lbs
- Meters without service disconnect
 - Individual meter 1.3 - 1.7 lbs
 - 4 meter pack 6.2 - 7.8 lbs
 - Pallet (120 meters) 200 - 255 lbs

I-210+

Basic Functions

- Basic function as electronic single phase Revenue Meter
- Four energy options (delivered, received, delivered+received, delivered -received)
- Tamper detect capability
- Broad communication module options
- Network applications
- Models available for 120 or 240 volt CL 20, CL 100, 200, CL 320 applications.
- 50 or 60 Hz operation

Optional Functions

- Factory integrated Service Switch Capability

Soft-Switch Functions

- AMR/AMI Communications (AMR/AMI Interface formats include quadrature pulse, PSEM, SPI Format-1 data, SPI Format-2 Data)
- Display AMR calculated Demand value shown on the lower 3 LCD digits
- Simple Voltage Event monitoring in addition to RMS momentary voltage display

Rating

- Voltage: 120V - 240V
- Current: Class 100, Class 200, Class 320, Class 20
- Frequency: 50 or 60 Hz

Cover Options

- Polycarbonate cover with molded sunshield
 - Plain cover without RESET or “D” ring
 - With Optocom “D” ring

Operating Range

- Voltage +/- 20%
- Operates over a broad temperature range (-40C through +85C under the cover)

Available Models


- ANSI Form 1S, 2S, 3S, 4S, 12S, 25S
- CL20, CL100, CL200, CL320

Applicable Standards

- Performance meets or exceeds industry standards ANSI C12.1
- ANSI C12.10
- ANSI C12.20
- ANSI C37.90.1

Technical Specifications

I-210+ (cont'd)

Soft-Switch Functions	
5 large characters to display the billing quantities	
	
Weights and Dimensions	
Dimensions 6.94 in. Max  5.25 in. Max	
Approximate Weight	
Meters with service disconnect	
- Individual meter	2.0 - 2.4 lbs
- 4 meter pack	9.0 - 10.6 lbs
- Pallet (120 meters)	285 -340 lbs
Meters without service disconnect	
- Individual meter	1.3 - 1.7 lbs
- 4 meter pack	6.2 - 7.8 lbs
- Pallet (120 meters)	200 -255 lbs

Aclara is a world-class supplier of smart infrastructure solutions (SIS) to more than 800 water, gas, and electric utilities globally. Aclara SIS offerings include smart meters and other field devices, advanced metering infrastructure and software and services that enable utilities to predict and respond to conditions, leverage their distribution networks effectively and engage with their customers. Aclara is owned by an affiliate of Sun Capital Partners.

Visit us at Aclara.com, phone 800 297 2728 or contact us at info@aclara.com and follow us on Twitter @AclaraSolutions.